

		Sprung			Shore		Art / Grösse								
Bezeichnung	Ø mm	ca. 20°	ca. 25°	Gewicht	A	C	KR	KL	KX	MR	ML	MX	GR	GL	GX
Pt 1	39,2	27	31	39,8	94	98					x				
Pt 2	39,0	40	45	40,6	62	74					x				
Pt 3	38,6	32	36	34,4	47	54		x							
Pt 4	39,0	43	47	41,8	46	59				x					
V_E7	39,3	29	30	56,1	95	98					x				
V_K1	38,7	38	46	35,4	40	48		x							
V_K10	39,0-39,5	35	42	35,2	38	48					x				
V I	39,2	45	48	35,4	43	52		x							
V III	39,2	39	43	45,7	46	62					x				
V III	39,0	33	37	42,4	53	67					x				
V III	39,2	33	37	42,9	55	68					x				
V IV	39,3	14	17	37,5	74	82				x					
V IV	39,3	14	17	36,8	70	81					x				
V 1	39,0	50	55	33,6	41	58				x					
V 1	39,4	53	56	36,7	52	67					x				
V 2	38,8	50	55	31,9	45	65		x							
V 3	38,6	54	56	36,2	42	66	x								
V 3	39,1	40	43	38,6	51	67					x				
V 3	38,9	46	51	37,4	51	72					x				
V 4	39,5	42	47	42,0	62	75					x				
V 7	39,2	46	53	43,7	64	80				x					
V 7	39,1-39,5	45	53	44,5	64	80					x				
V 8	39,0-39,2	47	48	48,7	81	92		x							
V 10	39,2	33	38	47,0	78	85					x				
V 11	38,9-39,0	32	39	46,3	79	88					x				
V 11	39,1	37	45	46,2	78	87					x				
V 13	39,4	14	20	37,8	66	81				x					
V 13	39,3	14	20	37,3	69	83					x				
V 15	39,0-39,2	15	15	38,4	90	97					x				
V 19	39,3	12	16	37,8	80	85					x				
V 21	39,2	38	41	35,4	44	49					x				
V 21	38,6	44	47	33,6	37	45					x				
V 24	39,2	12	15	37,2	76	90					x				
V 28	39,3	45	52	36,0	55	66					FI				
V 28	40,0-40,3	46	50	37,4	51-58	63-67					FI				
V 29	38,6-38,9	28	34	45,7	59	70		FI							
V 30	39,6	35	38	89,7	70	83					x				
V 250	39,0	48	55	35,0	50	63					x				
V 260	38,5	43	49	32,5	35	42	x								
V 260	38,6	40	45	33,7	45	52		x							

		Sprung			Shore		Art / Grösse								
Bezeichnung	Ø mm	ca. 20°	ca. 25°	Gewicht	A	C	KR	KL	KX	MR	ML	MX	GR	GL	GX
V 270	38,1	30	37	40,4	45	59	x								
V 270	38,6-38,7	32	41	41,8	49	61		x							
V 270	38,3-38,5	32	41	41,8	49	61		x							
V 330	39,5-40,0	40	46	92,6	51-62	65-70					x				
V 330	39,5-40,0	40	46	91,8	65	78					x				